


Probability rules


FUNDAMENTALS OF BAYESIAN DATA ANALYSIS IN R



Rasmus Bååth

Data Scientist





Bad and good news


- Bad news
 - The computation method we've used scales horribly.
- Good news
 - Bayesian computation is a hot research topic.
 - There are many methods to fit Bayesian models more efficiently.
 - The result will be the same, you'll just get it faster.

Probability theory

- Probability
 - A number between 0 and 1.
 - A statement of certainty/uncertainty.
- Mathematical notation:
 - $P(n_{\text{visitors}} = 13)$ is a probability
 - $P(n_{\text{visitors}})$ is a probability *distribution*
 - $P(n_{\text{visitors}} = 13 | \text{prop_clicks} = 10\%)$ is a *conditional* probability
 - $P(n_{\text{visitors}} | \text{prop_clicks} = 10\%)$ is a *conditional* probability *distribution*

$P(n_{\text{visitors}} \mid \text{prop_clicks} = 10\%)$

```
n_visitors <- rbinom(n = 10000, size = 100, prob = 0.1)  
hist(n_visitors)
```



Manipulating probability

Manipulating probability

- The sum rule

Manipulating probability

- The sum rule
 - $p(1 \text{ or } 2 \text{ or } 3)$

Manipulating probability

- The sum rule
 - $p(1 \text{ or } 2 \text{ or } 3) = 1/6 + 1/6 + 1/6 = 0.5$

Manipulating probability

- The sum rule
 - $p(1 \text{ or } 2 \text{ or } 3) = 1/6 + 1/6 + 1/6 = 0.5$
- The product rule

Manipulating probability

- The sum rule
 - $p(1 \text{ or } 2 \text{ or } 3) = 1/6 + 1/6 + 1/6 = 0.5$
- The product rule
 - $p(6 \text{ and } 6)$

Manipulating probability

- The sum rule
 - $p(1 \text{ or } 2 \text{ or } 3) = 1/6 + 1/6 + 1/6 = 0.5$
- The product rule
 - $p(6 \text{ and } 6) = 1/6 * 1/6 = 1 / 36 = 2.8\%$

Manipulating probability

- The sum rule
 - $p(1 \text{ or } 2 \text{ or } 3) = 1/6 + 1/6 + 1/6 = 0.5$
- The product rule
 - $p(6 \text{ and } 6) = 1/6 * 1/6 = 1 / 36 = 2.8\%$
- **Foundations of Probability in R**

Let's try out these rules!

FUNDAMENTALS OF BAYESIAN DATA ANALYSIS IN R

We can calculate!

FUNDAMENTALS OF BAYESIAN DATA ANALYSIS IN R



Rasmus Bååth

Data Scientist

Simulation vs calculation

- Simulation using 'r'-functions, for example, `rbinom` and `rpois`
- Simulating $P(\text{n_visitors} = 13 | \text{prob_success} = 10\%)$

```
n_visitors <- rbinom(n = 100000, size = 100, prob = 0.1)
sum(n_visitors == 13) / length(n_visitors)
```

0.074

- Calculation using the 'd'-functions, for example, `dbinom` and `dpois`
- Calculating $P(\text{n_visitors} = 13 | \text{prob_success} = 10\%)$

```
dbinom(13, size = 100, prob = 0.1)
```

0.074

- Calculating $P(\text{n_visitors} = 13 \text{ or } \text{n_visitors} = 14 | \text{prob_success} = 10\%)$

```
dbinom(13, size = 100, prob = 0.1) + dbinom(14, size = 100, prob = 0.1)
```

0.126

- Calculating $P(\text{n_visitors} | \text{prop_success} = 10\%)$

```
n_visitors = seq(0, 100, by = 1)
probability <- dbinom(n_visitors, size = 100, prob = 0.1)
```

n_visitors


0 1 2 3 4 5 6 7 ...

probability

0.000 0.000 0.002 0.006 0.016 0.034 0.060 0.089 ...

Plotting a calculated distribution


```
plot(n_visitors, probability, type = "h")
```



Continuous distributions

- The Uniform distribution

```
x <- runif(n = 100000, min = 0.0, max = 0.2)  
hist(x)
```



Continuous distributions

- The Uniform distribution
 - The d-version of `runif` is `dunif`:

```
dunif(x = 0.12, min = 0.0, max = 0.2)
```

5

- Probability *density*: Kind of a relative probability

```
x = seq(0, 0.2, by=0.01)  
dunif(x, min = 0.0, max = 0.2)
```

Try this out!

FUNDAMENTALS OF BAYESIAN DATA ANALYSIS IN R


Bayesian calculation


FUNDAMENTALS OF BAYESIAN DATA ANALYSIS IN R



Rasmus Bååth

Data Scientist





Bayesian inference by calculation

Bayesian inference by calculation

```
n_ads_shown <- 100
```

Bayesian inference by calculation

```
n_ads_shown <- 100  
n_visitors  
proportion_clicks
```

Bayesian inference by calculation

```
n_ads_shown <- 100  
n_visitors <- seq(0, 100, by = 1)  
proportion_clicks
```

Bayesian inference by calculation

```
n_ads_shown <- 100  
n_visitors <- seq(0, 100, by = 1)  
proportion_clicks <- seq(0, 1, by = 0.01)
```

Bayesian inference by calculation

```
n_ads_shown <- 100  
n_visitors <- seq(0, 100, by = 1)  
proportion_clicks <- seq(0, 1, by = 0.01)  
pars <- expand.grid(proportion_clicks = proportion_clicks,  
                     n_visitors = n_visitors)
```

proportion_clicks	n_visitors
0.04	38
0.11	93
0.16	100
0.67	98
0.96	3
0.48	73
0.14	13
...	...

Bayesian inference by calculation

```
n_ads_shown <- 100  
n_visitors <- seq(0, 100, by = 1)  
proportion_clicks <- seq(0, 1, by = 0.01)  
pars <- expand.grid(proportion_clicks = proportion_clicks,  
                     n_visitors = n_visitors)  
proportion_clicks <- runif(n_samples, min = 0.0, max = 0.2)
```

proportion_clicks	n_visitors
0.04	38
0.11	93
0.16	100
0.67	98
0.96	3
0.48	73
0.14	13
...	...

Bayesian inference by calculation

```
n_ads_shown <- 100
n_visitors <- seq(0, 100, by = 1)
proportion_clicks <- seq(0, 1, by = 0.01)
pars <- expand.grid(proportion_clicks = proportion_clicks,
                     n_visitors = n_visitors)
pars$prior <- dunif(pars$proportion_clicks, min = 0, max = 0.2)
```

proportion_clicks	n_visitors	prior
0.04	38	5
0.11	93	5
0.16	100	5
0.67	98	0
0.96	3	0
0.48	73	0
0.14	13	5
...

Bayesian inference by calculation

```
n_ads_shown <- 100
n_visitors <- seq(0, 100, by = 1)
proportion_clicks <- seq(0, 1, by = 0.01)
pars <- expand.grid(proportion_clicks = proportion_clicks,
                     n_visitors = n_visitors)
pars$prior <- dunif(pars$proportion_clicks, min = 0, max = 0.2)
n_visitors <- rbinom(n = n_samples, size = n_ads_shown,
                      prob = proportion_clicks)
```

proportion_clicks	n_visitors	prior
0.04	38	5
0.11	93	5
0.16	100	5
0.67	98	0
0.96	3	0
0.48	73	0
0.14	13	5
...

Bayesian inference by calculation

```
n_ads_shown <- 100
n_visitors <- seq(0, 100, by = 1)
proportion_clicks <- seq(0, 1, by = 0.01)
pars <- expand.grid(proportion_clicks = proportion_clicks,
                     n_visitors = n_visitors)
pars$prior <- dunif(pars$proportion_clicks, min = 0, max = 0.2)
pars$likelihood <- dbinom(pars$n_visitors, size = n_ads_shown,
                           prob = pars$proportion_clicks)
```

proportion_clicks	n_visitors	prior	likelihood
0.04	38	5	3.409439e-27
0.11	93	5	5.006969e-80
0.16	100	5	2.582250e-80
0.67	98	0	4.863666e-15
0.96	3	0	3.592054e-131
0.48	73	0	2.215148e-07
0.14	13	5	1.129620e-01
...

Bayesian inference by calculation

```
n_ads_shown <- 100
n_visitors <- seq(0, 100, by = 1)
proportion_clicks <- seq(0, 1, by = 0.01)
pars <- expand.grid(proportion_clicks = proportion_clicks,
                     n_visitors = n_visitors)
pars$prior <- dunif(pars$proportion_clicks, min = 0, max = 0.2)
pars$likelihood <- dbinom(pars$n_visitors, size = n_ads_shown,
                           prob = pars$proportion_clicks)
pars$probability <- pars$likelihood * pars$prior
```

proportion_clicks	n_visitors	prior	likelihood	probability
0.04	38	5	3.409439e-27	1.704720e-26
0.11	93	5	5.006969e-80	2.503485e-79
0.16	100	5	2.582250e-80	1.291125e-79
0.67	98	0	4.863666e-15	0.000000e+00
0.96	3	0	3.592054e-131	0.000000e+00
0.48	73	0	2.215148e-07	0.000000e+00
0.14	13	5	1.129620e-01	5.648101e-01
...

Bayesian inference by calculation

```
n_ads_shown <- 100
n_visitors <- seq(0, 100, by = 1)
proportion_clicks <- seq(0, 1, by = 0.01)
pars <- expand.grid(proportion_clicks = proportion_clicks,
                     n_visitors = n_visitors)
pars$prior <- dunif(pars$proportion_clicks, min = 0, max = 0.2)
pars$likelihood <- dbinom(pars$n_visitors, size = n_ads_shown,
                           prob = pars$proportion_clicks)
pars$probability <- pars$likelihood * pars$prior
sum(pars$probability)
```

105

proportion_clicks	n_visitors	prior	likelihood	probability
0.04	38	5	3.409439e-27	1.704720e-26
0.11	93	5	5.006969e-80	2.503485e-79
0.16	100	5	2.582250e-80	1.291125e-79
0.67	98	0	4.863666e-15	0.000000e+00
0.96	3	0	3.592054e-131	0.000000e+00
0.48	73	0	2.215148e-07	0.000000e+00
0.14	13	5	1.129620e-01	5.648101e-01
...

Bayesian inference by calculation

```
n_ads_shown <- 100
n_visitors <- seq(0, 100, by = 1)
proportion_clicks <- seq(0, 1, by = 0.01)
pars <- expand.grid(proportion_clicks = proportion_clicks,
                     n_visitors = n_visitors)
pars$prior <- dunif(pars$proportion_clicks, min = 0, max = 0.2)
pars$likelihood <- dbinom(pars$n_visitors, size = n_ads_shown,
                           prob = pars$proportion_clicks)
pars$probability <- pars$likelihood * pars$prior
pars$probability <- pars$probability / sum(pars$probability)
```


proportion_clicks	n_visitors	prior	likelihood	probability
0.04	38	5	3.409439e-27	1.623542e-28
0.11	93	5	5.006969e-80	2.384271e-81
0.16	100	5	2.582250e-80	1.229643e-81
0.67	98	0	4.863666e-15	0.000000e+00
0.96	3	0	3.592054e-131	0.000000e+00
0.48	73	0	2.215148e-07	0.000000e+00
0.14	13	5	1.129620e-01	5.379144e-03
...


Bayesian inference by calculation

```
n_ads_shown <- 100
n_visitors <- seq(0, 100, by = 1)
proportion_clicks <- seq(0, 1, by = 0.01)
pars <- expand.grid(proportion_clicks = proportion_clicks,
                     n_visitors = n_visitors)
pars$prior <- dunif(pars$proportion_clicks, min = 0, max = 0.2)
pars$likelihood <- dbinom(pars$n_visitors, size = n_ads_shown,
                           prob = pars$proportion_clicks)
pars$probability <- pars$likelihood * pars$prior
pars$probability <- pars$probability / sum(pars$probability)
sum(pars$probability)
```

1

proportion_clicks	n_visitors	prior	likelihood	probability
0.04	38	5	3.409439e-27	1.623542e-28
0.11	93	5	5.006969e-80	2.384271e-81
0.16	100	5	2.582250e-80	1.229643e-81
0.67	98	0	4.863666e-15	0.000000e+00
0.96	3	0	3.592054e-131	0.000000e+00
0.48	73	0	2.215148e-07	0.000000e+00
0.14	13	5	1.129620e-01	5.379144e-03
...






```
n_ads_shown <- 100
n_visitors <- seq(0, 100, by = 1)
proportion_clicks <- seq(0, 1, by = 0.01)
pars <- expand.grid(proportion_clicks = proportion_clicks,
                     n_visitors = n_visitors)
pars$prior <- dunif(pars$proportion_clicks, min = 0, max = 0.2)
pars$likelihood <- dbinom(pars$n_visitors, size = n_ads_shown,
                           prob = pars$proportion_clicks)
pars$probability <- pars$likelihood * pars$prior
pars$probability <- pars$probability / sum(pars$probability)
```


proportion_clicks	n_visitors	prior	likelihood	probability
0.04	38	5	3.409439e-27	1.623542e-28
0.11	93	5	5.006969e-80	2.384271e-81
0.16	100	5	2.582250e-80	1.229643e-81
0.67	98	0	4.863666e-15	0.000000e+00
0.96	3	0	3.592054e-131	0.000000e+00
0.48	73	0	2.215148e-07	0.000000e+00
0.14	13	5	1.129620e-01	5.379144e-03
...

```
n_ads_shown <- 100
n_visitors <- seq(0, 100, by = 1)
proportion_clicks <- seq(0, 1, by = 0.01)
pars <- expand.grid(proportion_clicks = proportion_clicks,
                     n_visitors = n_visitors)
pars$prior <- dunif(pars$proportion_clicks, min = 0, max = 0.2)
pars$likelihood <- dbinom(pars$n_visitors, size = n_ads_shown,
                           prob = pars$proportion_clicks)
pars$probability <- pars$likelihood * pars$prior
pars$probability <- pars$probability / sum(pars$probability)
pars <- pars[pars$n_visitors == 13, ]
pars$probability <- pars$probability / sum(pars$probability)
```


proportion_clicks	n_visitors	prior	likelihood	probability
0.04	13	5	1.368611e-04	0.0001428716
0.14	13	5	1.129620e-01	0.1179229621
0.19	13	5	3.265098e-02	0.0340849069
0.39	13	0	7.234996e-09	0.0000000000
0.59	13	0	1.531703e-21	0.0000000000
0.79	13	0	3.582066e-45	0.0000000000
0.94	13	0	1.591196e-91	0.0000000000
...




Calculated posterior



Calculated posterior



Simulated posterior



Calculate for yourself!

FUNDAMENTALS OF BAYESIAN DATA ANALYSIS IN R

Bayes' theorem

FUNDAMENTALS OF BAYESIAN DATA ANALYSIS IN R



Rasmus Bååth

Data Scientist

This is Bayes' theorem!

```
pars$probability <- pars$likelihood * pars$prior  
pars$probability <- pars$probability / sum(pars$probability)
```

This is Bayes' theorem!

```
pars$probability <- pars$likelihood * pars$prior  
pars$probability <- pars$probability / sum(pars$probability)
```

$$P(\theta|D)$$

The probability of **different parameter values**
given some **data**

This is Bayes' theorem!

```
pars$probability <- pars$likelihood * pars$prior  
pars$probability <- pars$probability / sum(pars$probability)
```

$$P(\theta|D) = \frac{P(D|\theta)}{\text{sum}(P(D|\theta))}$$

The probability of **different parameter values**
given some **data**
= equals =

The likelihood: The (relative) probability of the data
given different parameter values

This is Bayes' theorem!

```
pars$probability <- pars$likelihood * pars$prior  
pars$probability <- pars$probability / sum(pars$probability)
```

$$P(\theta|D) = \frac{P(D|\theta) \times P(\theta)}{\text{sum}(P(D|\theta) \times P(\theta))}$$

The probability of **different parameter values**
given some **data**
= equals =

The likelihood: The (relative) probability of the data
given different parameter values
× times ×

The prior: The probability of different parameters
before seeing the data

This is Bayes' theorem!

```
pars$probability <- pars$likelihood * pars$prior  
pars$probability <- pars$probability / sum(pars$probability)
```

$$P(\theta|D) = \frac{P(D|\theta) \times P(\theta)}{\sum P(D|\theta) \times P(\theta)}$$

The probability of **different parameter values**
given some **data**
= equals =

The likelihood: The (relative) probability of the data
given different parameter values
× times ×

The prior: The probability of different parameters
before seeing the data
/ divided by /

The total sum of the likelihood weighted by the prior.

This is Bayes' theorem!

$$P(\theta|D) = \frac{P(D|\theta) \times P(\theta)}{\sum P(D|\theta) \times P(\theta)}$$

BAYES

THEOREM

Grid approximation

- Define a grid over all the parameter combinations you need to evaluate.
- Approximate as it's often impossible try all parameter combinations.
- (There are many more algorithms to fit Bayesian models, some more efficient than others...)

A mathematical notation for models

$$n_{\text{ads}} = 100$$

$$p_{\text{clicks}} \sim \text{Uniform}(0.0, 0.2)$$

$$n_{\text{visitors}} \sim \text{Binomial}(n_{\text{ads}}, p_{\text{clicks}})$$

**Up next: More
parameters, more
data!**

FUNDAMENTALS OF BAYESIAN DATA ANALYSIS IN R